

6 PT STANDARD

SHOCKWAVE Impact Duty™ 3/4" Drive Standard Sockets

Part Number	Optional Retaining Ring	Description	Depth	Diameter	Type	L	D1	D2	Min Hex Depth
49-66-6300	49-66-6743	3/4" Drive	Standard	9/16"	A	53	27	41.4	6.3
49-66-6301		3/4" Drive	Standard	5/8"	A	53	29.9	41.4	7.1
49-66-6302		3/4" Drive	Standard	11/16"	A	53	30.7	41.4	8.1
49-66-6303		3/4" Drive	Standard	3/4"	A	53	32	41.4	9
49-66-6304		3/4" Drive	Standard	13/16"	A	53	34.9	41.4	10.6
49-66-6305		3/4" Drive	Standard	7/8"	A	53	36	41.4	12.2
49-66-6306		3/4" Drive	Standard	15/16"	A	53	38	41.4	12.4
49-66-6307		3/4" Drive	Standard	1"	A	53	40	41.4	12.4
49-66-6308	49-66-6744	3/4" Drive	Standard	1-1/16"	A	53	40.5	44.2	12.4
49-66-6309		3/4" Drive	Standard	1-1/8"	B	53	44.2	44.2	16.1
49-66-6310		3/4" Drive	Standard	1.3/16"	B	53	46	44.2	16.1
49-66-6311		3/4" Drive	Standard	1-1/4"	B	53	48	44.2	16.1
49-66-6312		3/4" Drive	Standard	1-5/16"	B	57	51	44.2	18.8
49-66-6313		3/4" Drive	Standard	1-3/8"	B	57	52	44.2	18.8
49-66-6314		3/4" Drive	Standard	1-7/16"	B	57	54.8	44.2	18.8
49-66-6315		3/4" Drive	Standard	1-1/2"	B	57	56	44.2	21.5
49-66-6316		3/4" Drive	Standard	1-9/16"	B	58	58	44.2	21.5
49-66-6317		3/4" Drive	Standard	1-5/8"	B	58	59	44.2	21.5
49-66-6318		3/4" Drive	Standard	1-11/16"	B	58	65	44.2	24.6
49-66-6319		3/4" Drive	Standard	1-3/4"	B	62	65	44.2	24.9
49-66-6320		3/4" Drive	Standard	1-13/16"	B	62	66	44.2	25.1
49-66-6321		3/4" Drive	Standard	1-7/8"	B	65	68	44.2	27
49-66-6322		3/4" Drive	Standard	1-15/16"	B	65	69.8	44.2	27.2
49-66-6323		3/4" Drive	Standard	2"	B	65	72	44.2	27

